



## S4/i S35 T2.0 Primes | Basic specification

Specifications	12mm	14mm	16mm	18mm	21mm	25mm	27mm	32mm	35mm
T-Stop range	T2 - T22	T2 - T22	T2 - T22	T2 - T22	T2 - T22	T2 - T22	T2 - T22	T2 - T22	T2 - T22
Angular rotation of iris scale	96°	96°	96°	96°	96°	96°	96°	96°	95°
Min. marked object distance	225 mm	225 mm	225 mm	250 mm	250 mm	250 mm	250 mm	325 mm	350 mm
	9in	9in	9in	9in	9in	9in	10 in	12 in	14 in
Angular rotation to MOD endstop	270°	300°	270°	300°	270°	300°	270°	300°	300°
Length from front of lens to PL lens mount	126 mm	122 mm	126 mm	107 mm	107 mm	107 mm	111 mm	123 mm	127 mm
	5 in	4.8 in	5 in	4.2 in	4.2 in	4.2 in	4.4 in	4.8 in	5 in
Max. front diameter	156 mm	110 mm	110 mm	110 mm	110 mm	110 mm	110 mm	110 mm	110 mm
	6.1in	4.3in	4.3in	4.3in	4.3in	4.3in	4.3 in	4.3 in	4.3 in
Max. diagonal angle of view for S35 format at 30mm image diagonal	103°	94°	86°	80°	71°	62°	58°	50°	46°
Total weight (with PL lens mount)	3 kg	2.2 kg	2.4 kg	1.7 kg	2.0 kg	1.6 kg	1.6 kg	1.8 kg	1.9 kg
	6.5 lbs	4.8 lbs	5.4 lbs	3.8 lbs	4.4 lbs	3.5 lbs	3.5 lbs	4 lbs	4.2 lbs
Screw-in filter	N/A	N/A	M105 x 0.75	M105 x 0.75	M105 x 0.75	M105 x 0.75	M105 x 0.75	M105 x 0.75	M105 x 0.75

Continued on next page →

Maximum format cover	30 mm diameter (Super35 format)
Focus scales	Imperial or Metric scales marked from infinity to MOD
Focus drive gear	140 teeth 0.8 metric module
Iris scales	Two opposing linear T-scales - whole and third stops marked
Iris drive gear	134 teeth 0.8 metric module
Mount	PL



## S4/i S35 T2.0 Primes | Basic specification

Specifications	40mm	50mm	65mm	75mm	100mm	135mm	150mm	180mm	300mm
T-Stop range	T2 - T22	T2 - T22	T2 - T22	T2 - T22	T2 - T22	T2 - T22	T2 - T22	T2 - T22	T2.8 - T22
Angular rotation of iris scale	94°	93°	92°	92°	91°	92°	92°	94°	78°
Min. marked object distance	450 mm	550 mm	700 mm	800 mm	950 mm	850 mm	1,050 mm	1,300 mm	2,100 mm
	16 in	20 in	2 ft 3 in	2 ft 6 in	3 ft	2 ft 9 in	3 ft 6 in	4 ft 3 in	7 ft
Angular rotation to MOD endstop	300°	300°	300°	300°	300°	340°	320°	320°	320°
Length from front of lens to PL lens mount	135 mm	120 mm	122 mm	120 mm	136 mm	184 mm	157 mm	185 mm	202 mm
	5.3 in	4.7 in	4.8 in	4.7 in	5.4 in	7.3 in	6.2 in	7.3 in	8 in
Max. front diameter	110 mm	110 mm	110 mm	110 mm	110 mm	110 mm	125 mm	136 mm	136 mm
	4.3 in	4.3 in	4.3 in	4.3 in	4.3 in	4.3 in	4.9 in	5.3 in	5.3 in
Max. diagonal angle of view for S35 format at 30mm image diagonal	41°	34°	26°	22°	17°	13°	11.5°	9.5°	5.7°
Total weight (with PL lens mount)	2 kg	1.5 kg	1.6 kg	1.7 kg	2 kg	2.2 kg	3.5 kg	4.3 kg	4.7 kg
	4.4 lbs	3.3 lbs	3.5 lbs	3.8 lbs	4.4 lbs	4.9 lbs	7.7 lbs	9.4 lbs	10.3 lbs
Screw-in filter	M105 x 0.75	M105 x 0.75	M105 x 0.75	M105 x 0.75	M105 x 0.75	M105 x 0.75	M120 x 1.0	M131 x 1.0	M131 x 1.0

Maximum format cover	30 mm diameter (Super35 format)
Focus scales	Imperial or Metric scales marked from infinity to MOD
Focus drive gear	140 teeth 0.8 metric module
Iris scales	Two opposing linear T-scales - whole and third stops marked
Iris drive gear	134 teeth 0.8 metric module
Mount	PL