



Anamorphic/i S35 T2.3 Primes (Squeeze factor 2x) | Basic specification

Specifications	25mm*	32mm	40mm	50mm	65mm Macro*
T-Stop range	T2.3 - T22	T2.3 - T22	T2.3 - T22	T2.3 - T22	T2.6 - T22
Angular rotation of iris scale	90°	90°	90°	90°	90°
Min. marked object distance	1,000 mm	850 mm	850 mm	850 mm	440 mm
	3 ft	2 ft 9 in	2 ft 9 in	2 ft 9 in	17 in
Angular rotation to MOD endstop	300°	300°	300°	300°	300°
Length from front of lens to PL lens mount	204 mm	198 mm	205 mm	205 mm	266 mm
	8 in	7.8 in	8.1 in	8.1 in	10.5 in
Max. front diameter	136 mm	110 mm	110 mm	110 mm	136 mm
	5.3 in	4.3 in	4.3 in	4.3 in	5.3 in
Max. angle of view (Horizontal/Vertical)	H96.9° / V41°	H77.5° / V32.6°	H62.8° / V26.3°	H50.7° / V21.2°	H36.9° / V15.6°
Total weight (with PL lens mount)	4.2 kg	3.2 kg	3.4 kg	3.6 kg	5.2 kg
	9.2 lbs	7.1 lbs	7.5 lbs	7.9 lbs	11.5 lbs
Screw-in filter	M131 x 0.75	N/A	M105 x 0.75	M105 x 0.75	M131 x 0.75

Continued on next page →

Maximum format cover	Super35, optimised for coverage of 31.1 mm
Focus scales	Dual Focus scales - Imperial and Metric, scales marked from infinity to MOD
Focus drive gear	140 teeth 0.8 metric module
Iris scales	Two opposing linear T-scales - whole and third stops marked
Iris drive gear	134 teeth 0.8 metric module
Mount	PL or LPL

***Supplied with support bracket**



Anamorphic/i S35 T2.3 Primes (Squeeze factor 2x) | Basic specification

Specifications	75mm	100mm	135mm*	180mm*	300mm*
T-Stop range	T2.3 - T22	T2.3 - T22	T2.3 - T22	T2.8 - T22	T3.5 - T22
Angular rotation of iris scale	90°	90°	90°	90°	90°
Min. marked object distance	1,000 mm	1,200 mm	1,400 mm	2,000 mm	3,000 mm
	3 ft 3 in	3 ft 9 in	5 ft	6 ft 6 in	10 ft
Angular rotation to MOD endstop	300°	300°	300°	300°	300°
Length from front of lens to PL lens mount	205 mm	205 mm	240 mm	302 mm	381 mm
	8.1 in	8.1 in	9.5 in	11.9 in	15 in
Max. front diameter	110 mm	110 mm	110 mm	110 mm	136 mm
	4.3 in	4.3 in	4.3 in	4.3 in	5.3 in
Max. angle of view (Horizontal/Vertical)	H34.1° / V14.1°	H25.7° / V10.7°	H19.1° / V7.90°	H13.9° / V5.70°	H8.5° / V3.5°
Total weight (with PL lens mount)	3.2 kg	3.4 kg	4.2 kg	5.8 kg	9.4 kg
	7.1 lbs	7.5 lbs	9.3 lbs	12.8 lbs	20.7 lbs
Screw-in filter	M105 x 0.75	M105 x 0.75	M105 x 0.75	M105 x 0.75	M131 x 0.75

Maximum format cover	Super35, optimised for coverage of 31.1 mm
Focus scales	Dual Focus scales - Imperial and Metric, scales marked from infinity to MOD
Focus drive gear	140 teeth 0.8 metric module
Iris scales	Two opposing linear T-scales - whole and third stops marked
Iris drive gear	134 teeth 0.8 metric module
Mount	PL or LPL

***Supplied with support bracket**