



## S8/i FF T1.4 Primes | Basic specification

Specifications	18mm*	21mm*	25mm	27mm	32mm	35mm
T-Stop range	T1.4 - T22	T1.4 - T22	T1.4 - T22	T1.4 - T22	T1.4 - T22	T1.4 - T22
Angular rotation of iris scale	90°	90°	90°	90°	90°	90°
Min. marked object distance	600 mm	600 mm	550 mm	600 mm	650 mm	700 mm
	2 ft	2 ft	22 in	2 ft	2 ft 3 in	2 ft 3 in
Angular rotation to MOD endstop	270°	270°	270°	270°	270°	270°
Length from front of lens to PL lens mount	200 mm	195 mm	162 mm	162 mm	157 mm	157 mm
	7.8 in	7.7 in	6.4 in	6.4 in	6.2 in	6.2 in
Max. front diameter	136 mm	125 mm	104 mm	104 mm	104 mm	104 mm
	5.4 in	4.9 in	4.1 in	4.1 in	4.1 in	4.1 in
Max. diagonal angle of view for FF format	99°	93°	81°	77°	67°	63°
Max. diagonal angle of view for S35 format at 30mm image diagonal	77°	72°	62°	57°	51°	45°
Total weight (with PL lens mount)	3.4 kg	3.5 kg	2.4 kg	2.6 kg	2.4 kg	2.4 kg
	7.4 lbs	7.6 lbs	5.3 lbs	5.7 lbs	5.3 lbs	5.3 lbs
Screw-in filter	N/A	M99 x 0.75	M99 x 0.75	M99 x 0.75	M99 x 0.75	M99 x 0.75
Maximum format cover	Full Frame and beyond, optimised for coverage of 46.3 mm (18mm optimised for 43.3 mm)					
Focus scales	Dual Focus scales - Imperial and Metric, scales marked from infinity to MOD					
Focus drive gear	140 teeth 0.8 metric module					
Iris scales	Two opposing linear T-scales - whole and third stops marked					
Iris drive gear	134 teeth 0.8 metric module					
Mount	PL or LPL					

Continued on next page



\*Supplied with support bracket



## S8/i FF T1.4 Primes | Basic specification

Specifications	40mm	50mm	65mm	75mm	100mm	135mm
T-Stop range	T1.4 - T22	T1.4 - T22	T1.4 - T22	T1.4 - T22	T1.4 - T22	T1.4 - T22
Angular rotation of iris scale	90°	90°	90°	90°	90°	90°
Min. marked object distance	650 mm	700 mm	750 mm	800 mm	850 mm	1,200 mm
	2 ft 3 in	2 ft 3 in	2 ft 6 in	2 ft 9 in	2 ft 9 in	4 ft
Angular rotation to MOD endstop	270°	270°	270°	270°	270°	270°
Length from front of lens to PL lens mount	157 mm	157 mm	157 mm	157 mm	157 mm	200 mm
	6.2 in	6.2 in	6.2 in	6.2 in	6.2 in	7.9 in
Max. front diameter	104 mm	104 mm	104 mm	104 mm	104 mm	104 mm
	4.1 in	4.1 in	4.1 in	4.1 in	4.1 in	4.1 in
Max. diagonal angle of view for FF format	56°	47°	37°	32°	25°	19°
Max. diagonal angle of view for S35 format at 30mm image diagonal	42°	34°	26°	23°	18°	13°
Total weight (with PL lens mount)	2.3 kg	2.5 kg	2.6 kg	2.4 kg	2.6 kg	3.2 kg
	5 lbs	5.5 lbs	5.7 lbs	5.3 lbs	5.7 lbs	7 lbs
Screw-in filter	M99 x 0.75	M99 x 0.75	M99 x 0.75	M99 x 0.75	M99 x 0.75	M99 x 0.75

Maximum format cover	Full Frame and beyond, optimised for coverage of 46.3 mm (18mm optimised for 43.3 mm)
Focus scales	Dual Focus scales - Imperial and Metric, scales marked from infinity to MOD
Focus drive gear	140 teeth 0.8 metric module
Iris scales	Two opposing linear T-scales - whole and third stops marked
Iris drive gear	134 teeth 0.8 metric module
Mount	PL or LPL